



**Accessories / Zubehör / Accessoires:**

<p>Set (4) rubber blocks Set (4) Gummi-Blöcke Set (4) rubber blokken</p>  <p><b>BA-RB80</b> (4x 160x120x80mm) <b>BA-RB120</b> (4x 160x120x120mm)</p>	<p>Set (2) Closed build-in cassette Set (2) Geschlossene Einbaukassette Set (2) Gesloten inbouw cassette Galvanized Galvanisiert Gegalvaniseerd</p>  <p>ASG4008: <b>BICCG4006/1600/260</b> ASG4008L: <b>BICCG4006/2100/290</b></p>	
<p>Set crossbeams to pick up 4WD vehicles Set Traversen auf 4WD Fahrzeuge abholen Set crossbeams voor opname 4WD voertuigen</p>	 <p><b>BA-A3/TRAV</b></p>	

**Technical specifications / Technische Spezifikationen / Technische specificaties:**

			<b>ASG4006</b>	
Capacity	Tragfähigkeit	Hefvermogen	4.000 kg	
Lifting time	Hebezeit	Heftijd	35 s	
Descent time	Absenkzeit	Daaltijd	40 s	
Noise level	Lärmpegel	Geluidsniveau	<74 dB (A) / 1 m	
Working temp.	Arbeitstemp.	Werktemp.	-10 °C / +50 °C	
Motor power	Motorleistung	Motorvermogen	2,2 kW	
Electr. Supply	Anschlußwert	Aansl. waarde	230/400V / 50Hz/ 3 Ph	
Color	Farbe	Kleur	RAL 5015	
Working envir.	Arbeitsumgeb.	Werkomgeving	Indoor/Drinnen/Binnen	

<p><b>Packing/Verpackung/Verpakking:</b></p>  <p><b>730 kg</b></p>	<p><b>Container transport:</b></p>  <p>20 ft. = 9 pieces/Stück/stuks</p>
---	---